

Physio Medical Instruments

Advance Physiotherapy Health care solutions







Health Solution with Ultramodern Technology

PHYSIOTHERAPY

- Totally feather touch panel for easy to operate unit.
- Light weight & Compaq PVC Body.
- Five mode of currents (Galvanic, Interrupted galvanic, Faradic, Surge Faradic & Tens)
- · SDC Facility available
- Best quality Bag

TREATMENT MODE:

- · Galvanic: Maximum output 0 to 145 volts DC
- Interrupted Galvanic: A Switch with select 9 different mode of frequency: (1,2,3,5,10,30,50,60,100 Hz)
- Pulse width: 0.01, 0.03, 0.10, 0.30, 0.40, 1, 3, 10, 30, 100, 300 Mili per seconds
- Faradic: 1 Mili Second pulsed width and 60 Hz.
 Frequency. Amplitude continuously adjustable from 0 to 145 volts.
- · Surge Faradic:
- Contraction Period: Adjustable from 1 to 9 seconds
- · Rest Period: Adjustable from 1 to 9 seconds
- Tens: Pulse width 400 micro sec & frequency 50 Hz.
- Buzzer: Audio buzzer at the end of treatment time.

LC704 MINI MUSCLE STIMULATOR WITH TENS



Also Available in Dual Channel

www.lifecarepmi.com



LC351 COMPUTERIZED MUSCLE STIMULATOR WITH TENS

TECHNICAL DETAIL:

· Input voltage: 230 VAC, 50 Hz

Dimensions: L 290mm x W 205mm x H 110mm

Weight: 2.0 Kg Approx

FREE ACCESSORIES:

· One pair plate Electrode



· One pair vecro straps

FEATURES:

- Three Different type of currents with variable surge duration.
- · User friendly can be easily operated.

TECHNICAL DETAIL:

Input voltage: 230VAC, 50 Hz

Dimensions: L 160mm x W 110mm x H 70mm

· Weight: 0.8 Kg Approx

TREATMENT MODE:

SF: 1 to 9 second Duration

· I.G.: pulse width: 100 mili second,

Frequency: 1 per second

TNS: pulse width: 400 Micro Sec., Frequency: 50 Hz

- One pair plate Electrode
- One point Electrode
- One pair velcro straps
- Best quality Bag

COMBINATION THERAPY UNIT:

- · Computerised Pannel Design with Feather Touch Key.
- · Large Graphic LCD Displgy.
- 100 Programmig And 99 Customize Program.
- · Prob Test Mode.

TREATMENT MODE:

- IFT: 2 Pole, 4 Pole, 4 Pole Vector and Russian Current.
- ULTRA SOUND 1Mhz: Contionues and pulse.
- TENS: Continuous & Burst Mode. (Frequency 1 to 250 Hz.)
- STIMULATION: Galvanic, Interuplted Galvanic, Surge Faradic, Faradic.
- · Diadynamic Current: CP, LP, DF, MF Modes Available.

TECHNICAL DETAIL:

- Input Voltage: 230 V AC, 50 Hz
- Dimensions L 390mm x W 390 mm x H 149mm
- · Weight: 6.7 Kg Approx

FREE ACCESORIES:

- IFT Cable with pad
- . Tens Cable with Pad
- Ultra Sound Applator
- Stimulator Cable





www.lifecarepmi.com



LC 902 COMBINATION THERAPY



FEATURES:

- · Individual Intensity for Two Channel.
- · Three Different type of currents.
- · Light Weight & Compact Pvc Body.
- · Best Quality Bag.

TECHNICAL DETAIL:

- Input Voltage: 230 VAC, 50Hz
- Dimensions: L160mm X W110mm X H70 mm
- · Weight: 0.8 Kg Approx

TREATMENT MODE:

- TENS: Pluse Width: 400 Micro Sec.
 Frequency: 10 Hz. to 100 Hz Adjustable.
- Interrupted Galavanic: Pulse Width 100 Mili Second Frequency: 1 Hz To 5 Adjustable.
- Surge Faradic: Contraction: 1 To 10 Sec.
 Frequency: 60 Hz, Pulse Width: 1.0 milli Sec.

- Two Pair Electrode
- One Point Electrode
- Two Pair Velcro Straps
- Best Quality Bag

- · Latest Computerised Tens Unit with Blue LCD Display
- Seven Different Type Of Currents with Variable Frequency and Pulse Width
- · Touch Switches for Comfort in Operation
- · Light weight & Compaq PVC Body. · Best quality Bag

TECHNICAL DETAIL:

- Input Supply: 230VAC, 50 Hz
- Size: L 290mm x W 205mm x H 110mm
- Weight: 1.5kg Approx
- Out Put Voltage: 0 to 50V with load of 500 Ohm
- · Pulse Width: 50 to 350 micro sec.
- Frequency: 16 to 200 Hz
- · Buzzer: Audio Buzzer at the end of treatment time.
- Seven Types of Mode (Continuous, Fast Burst, Slow Burst, Ramp, Sweep, Frequency & Pulse Width Modulation

FREE ACCESSORIES:

- · Four Pair Rubber Electrodes, Four Velcro Straps
- · One Gel Bottle. One Mains Cord

LC504 COMPUTERISED TWO CHANNEL TENS



www.lifecarepmi.com



LC270 COMPUTERISED FOUR CHANNEL TENS



FEATURES:

- Latest Computerised Tens Unit with Blue LCD Display
- Seven Different Type Of Currents with Variable Frequency and Pulse Width
- · Touch Switches for Comfort in Operation

TECHNICAL DETAIL:

- Input Voltage: 230 VAC, 50 Hz
- Size: L 185mm x W 120mm x H 80mm
- Weight: 1.3kg Approx

TREATMENT MODE:

- Seven Types of Mode (Continuous, Fast Burst, Slow Burst, Ramp & Sweep) Frequency & PW Modulation
- Pulse Width: 50 to 350 Micro Sec.
- Frequency: 16 to 200 Hz
- Buzzer: Audio Buzzer at the end of treatment time.

- Two Pairs of Rubber Electrodes
- · Two Pairs of Velcro Straps
- One Bottle of Electrode Gel
- Carry Bag

- · 27 Clinical Programmes
- · Manual Mode:

Continuous, Pulse - 1:1, 1:3, 1:4, 1:9

• Time: 1 to 30 minutes

- Encoder Based Design
- · Back Light Blue LCD Display

TECHNICAL DETAIL:

• Input Voltage: 230VAC, 50 Hz

Dimention: L 290 mm x W 205 mm x H 110 mm

· Output Mode: continuous and pulse

· Audio Buzzer at the End of Treatment Time

Frequency: 1 Mhz ApproxWeight: 3.0 kg Approx

FREE ACCESSORIES:

- Ultra Sonic Gel
- · Applicator with Cord

LC 360 (A) PORTABLE COMPUTERISED ULTRA SOUND 1 Mhz THERAPY



www.lifecarepmi.com



LC 360 COMPUTERISED ULTRA SOUND 1 Mhz THERAPY



FEATURES:

- · 27 Clinical Programmes
- Manual Mode:

Continuous, Pulse - 1:1, 1:3, 1:4, 1:9

- Time: 1 to 30 minutes
- · Encoder Based Design
- Back Light Blue LCD Display
- Light Weight and Compaq PVC Body

TECHNICAL DETAIL:

Input Voltage: 230 VAC, 50 Hz

Dimension: L195 mmxW150 mmXH 90 mm

Weight: 1.5 kg Approx.

Output mode: continuous and pulse.

· Audio Buzzer at the end of treatment time.

Frequency: 1 Mhz Approx.

- Ultra Sonic Gel
- Applicator with cord.
- Best quality

- Latest Computerized traction unit with Blue LCD Display
- Computerized Hold, Rest and Treatment time selection
- · Used in cervical, Lumber and Ankle Traction Treatment
- Patient Safety switch available

TECHNICAL DETAIL:

- Input voltage:230VAC, 50 Hz
- Dimensions: L 330 mm x W 260 mm x H 300 mm
- Weight: 11.5 Kg Approx

TREATMENT MODE: Intermittent & Static Mode

- Traction Force: 5 Kg to 45 Kg
- Hold Time: 20,30,40,50,60,70,80 Second
- Rest Time: 1 to 20 Second
- Time: 0 to 60 Minutes
 - Table Size: L 7.5"xW 2.0" xH 2.25"

FREE ACCESSORIES:

- · Cervical Spreader Bar
- · Chest and pelvic Belt
- · Cervical collar and Ankle Belt

LC900 CONTINUOUS PASSIVE MOTION UNIT



www.lifecarepmi.com



LC135 COMPUTERIZED LUMBER-CERVICAL-ANKLE TRACTION UNIT



FEATURES:

- Silent motor for noise free operation
- Patient Safely switch available
- Indication for up & down movement
- Manual flexion and extension adjustable

TECHNICAL DETAIL:

- Input voltage: 230 VAC, 50Hz
- Dimensions: L 11.5" x W 9.5" x H 4.25"
- Weight: 17.0 Kg. Approx
- Buzzer: Audio buzzer at the end of treatment time.

TREATMENT MODE:

- Flexion Hold Time: 1 Sec. / 5 Sec. / 10 Sec. / 15 Sec.
- Extension Hold Time: 1 to 10 Second
- Flexion Angle: 10 to 120
- Treatment Time: 0 to 60 Minutes



LC 641 GAIT TRANER



- Single Motor Function For Height Adjustment.
- · Remote Control Operated.
- · Heavy Duty Lockable Castor Wheel.
- · Treadmill Can Be Attached.
- · Lift Patient Up to 250kg.
- Best Quality Belt For Lifting Patient.

www.lifecarepmi.com

Specification:

- Frame : Heavy Duty Metal Frame.
- · Height Of The Main Frame 225cm.
- · Weighing Capasity 250kgs.
- Hanging Lifting Range 0 To 70cm.
- Lifting Mechanism Electric DC Oprated Motor.
- Input Voltage: 230v AC 50Hz.
- Dimensions: L 100 X B 110 X H 225cm.



- Economical, Most Advance, Powerfull & Efficetive Class IV Laser Therapy.
- · Colour Touch Screen Oprated.
- · Safety Switch Available.
- Usefull In Pain Relief, Trigger Points And Accupuncture Points.
- · Improved Metabolic Activity, Accelerated Tissue Repair.
- · Safety Goggles For Operator And Patient.

TECHNICAL DETAIL:

- Input Voltage 230 V Ac, 50 Hz.
- · Wave Lenth: 1064nm.
- Dimension: 35cm X 29cm X 17cm.
- Pulse Width: 1 200ms.
- · Working Mode: Continuous And Pulsed.

FREE ACCESORIES:

- · Handle With Cable.
- · Power Cable & Key.
- · Goggles For Operator And Patient.

LC 117 LASER WITH MICRO CURRENT



www.lifecarepmi.com



LC 221 DEEP TISSU-CLASS IV LASER THERAPY



- Low Level Therapy And Micro Current Proven to Be More Effective In Stimulating ATP Production.
- Safe And Alternative Method to Surgery And Pain Meditation.
- · No Side Effect.
- · Battery Operated Disgn.
- · Android Charger.
- · Micro Current Intensity Adjustable In 5 Steps.
- · Colour LCD Display And Feathour Touch Keys.
- · Weight: 100gms Aprox.
- · Class II Medical Device.
- · Type Red Laser Diode.
- Frequency: 690nm ± 5nm.
- · Micro Current: Pulsed Rectangular.
- · Battery: Lithium Ion Chargable.
- · 2 Minutes Auto Cut Off.

- Computerised Pannel design with Feather touch switches for comfort in operation.
- · Large graphic LCD based model
- 16 Various clinical treatment programmes
- · Light weight and Compaq PVC Body.
- Encoder Based Design

TECHNICAL DETAIL:

- Input Voltage: 230 VAC, 50 Hz
- Dimension: L 290 mm x W 205 mm x H 110 mm
- Inbuilt SMPS Power Supply Weight: 1.4 kg Approx.

TREATMENT MODE:

- Five Modes: 2 Pole, 4Pole, 4Pole 45% Vector, 4 Pole 90% Vector and Russian Current.
- · Base, Sweep, Ramp, On time and Off time adjustable.
- Balance facility available for both the channel 1 & 2.
- 1 to 99 minutes timer and Audio Buzzer at the end of treatment time.

FREE ACCESSORIES:

- Two pair Electrode Cables
- Velcro Straps and gel
- · Best quality bag
- Rubber pads 4 nos
- Mains cord wire

LC 603 (A) PORTABLE COMPUTERISED INTERFERNTIAL THERAPY UNIT



www.lifecarepmi.com



LC 621 COMPUTERISED INTERFERNTIAL THERAPY UNIT



FEATURES:

- Computerised Pannel Design With touch key for comfort in operation (with LED Indication)
- Light weight compact design for home visit, Clinical & Hospital.
- Large graphic LCD display.
- Light weight and Compaq PVC Body.
- · Encoder Based Design

TECHNICAL DETAIL:

- Input Voltage: 230 VAC, 50 Hz
- Dimension: L 195 mm x W 150 mm x H 90 mm
- Inbuilt SMPS Power Supply
 Weight: 1.2 kg Approx.

TREATMENT MODE :

- Five Modes: 2 Pole, 4Pole, 4Pole 45% Vector, 4 Pole 90% Vector and Russian Current.
- Base, Sweep, Ramp, On time and Off time adjustable.
- Balance facility available for both the channel 1 & 2.
- 1 to 99 minutes timer and Audio Buzzer at the end of treatment time.

- Two pair Electrode Cables
- Rubber pads 4 nos
- Velcro Straps and gel
- · Best quality bag



LC 261 (A) SIX LAMP INFRARED UNIT



Features:

- High & Low Intensity controller
- · Height, Angle and Direction Adjustable
- · Castor Wheeled Floor Model
- · High Speed Cooling Fan

Specification:

- 6 Infrared Lamp.
- Digital Timer: 1 to 30 Minutes.
- · Separate On/Off Switch.

Technical Detail:

- Input Voltage: 230V AC 50HZ
- Weight: 30.0 kg ApproxIR Lamp: 250 Watts

LC 018 DEEP HEAT THERAPY



www.lifecarepmi.com

FEATURES:

- · High quality pads with special safety insulation.
- 5 channels, 5 Pads (1 for Abdomen & Buttocks)
- · 2 for Thighs & 2 for Arms.

TECHNICAL DETAIL:

- Input voltage: 230 VAC, 50 Hz
- Time: 0 to 60 minutes Digital Time with Audio Buzzer
- · Temperature Controller for Heat Control.
- Dimensions:L315 mm xW260 mmxH130 mm
- Weight: 5.0 kg. Approx

- 5 Pads (1 for Abdomen & Buttocks)
- · 2 for Thighs & 2 for Arms.
- Mains Cord

- Elegant Square shaped Body
- Automatic Temperature 30° to 110° Control
- · Castor wheel for easy mobility
- · Corrosion & Leakage Proof
- Mains Indicator for mains supply and Heater Indicator for Heater Supply
- Highly Insulated double wall powder coated MS/SStank

TECHNICAL DETAIL:

Input voltage: 230 VAC, 50 HZ

• Dimensions:L350mmxW350mmxH190mm

Weight: 10 Kg. Approx (without Paraffin Wax)

FREE ACCESSORIES:

· Metal Trey and Brush





FEATURES:

- Automatic Temperature 30° to 110° control.
- Mains Indicator for mains supply and Heater Indicator for Heater Supply.
- Heavy gauge metal tank with powder coating.

TECHNICAL DETAIL:

Input Voltage: 230 V AC, 50 Hz

Dimension: L 240 mm x W 350 mm x H 245 mm
 Weight: 7.0 kg Approx. (without Paraffin wax)

FREE ACCESSORIES:

Metal tray and brush.



- · Easy to operate design.
- · Large LCD Display With 20 Programms.

TECHNICAL DETAIL:

- Input voltage: 230 VAC, 50 Hz.
- Dimension: 294 mm X 292 mm X 110 mm.
- Weight: 4 Kg. Approx.Frequency: 1 MHZOutput: 10 Watts.

FREE ACCESSORIES:

- · Applicator With Cable.
- · Inactive Electrode with Cable.
- · Jelly For Long Wave.





LONG WAVE DIATHERMY UNIT

LC205



FEATURES:

- Highly User Friendly Control Pannel For Ultrasound Therapy In 50 Customer Designed Therapeutic Protocols.
- Continuous and pulse Mode.
- Pulse Rate: 10 to 150 Hz Instep of 10 Hz.
- Pulse Peak: (Duty cycle 5-100% Instep of 5 %).
- Ergonomic Head with 1 & 3 MHZ.

TECHNICAL DETAIL:

- Input voltage: 230 VAC, 50 Hz.
- Dimension: 310 mm X 85 mm X 210 mm.
- · Audio Buzzer At The And Of Treatment Time.
- Frequency: 1 & 3 MHZ.
- · Weight: 2 Kg. Approx.

FREE ACCESSORIES:

- · Ultrasound Head 1 & 3 Combined.
- · Ultrasound Gel.

- · Preset Protocols.
- · Treatment Guidance With Photos.
- · Ergonomic Hand Piece.
- · Touch Screen Operated.
- Mode: Elbow, Knee, Shoulder, Hip,
 Pubic Symphsis, Hand, Lumber, Foot Akle.

TECHNICAL DETAIL:

- Input Voltage 230 V Ac, 50 Hz.
- · Weight: 4.0 Kg. Approx.
- Dimension: L300mm X W290mm X H250mm.
- · Frequency And Energy Level Adjustable.
- Frequency: 1 to 16 Hz.

FREE ACCESORIES:

- · Shock Wave Head.
- 5 Hand Piece
- · Foot Switch.

LC 270 COMPRESSIBLE SIX CHAMBER LIMB THERAPY



www.lifecarepmi.com



LC 254 SHOCK WAVE THERAPY



FEATURES:

- · User Friendly Touch Pannel.
- Six Modes: A,B,C,D,E,F.
- Oparate With Remote Control.
- Pressure: 30 To 240 mm Hg.
- Mode: Normal, Sequental Sequezze, Duble Wave, Whole Squere, Sequental Squere + Double Wave, Normal + Double + Whole Squere.

TECHNICAL DETAIL:

- Input Voltage 230 V Ac, 50 Hz.
- Time: 1 to 99 Min.
- · Weight: 2.0 Kg. Approx.

- Leg Cuff With Hose Pipe.
- · Hand Glows With Hose Pipe.
- · Waist Cuff With Hose Pipe.
- · Remote Control.





LC 252 TREATMENT TABLE (3 SECTION)








DESCRIPTION:

- Hydraullical System For Height Up And Down.
- Three Actuator For Height And Angle Adjustment.
- · Best Quality Steel And Powder Coating.
- · Equiped With Breathing Hole And Shoulder Support.
- · Operated With Remote Control.
- Swivelling Castors With Locking Brake System.
- · Noice Free Smooth Operating.
- · Synthetic Leather Upholstery.
- It Can Be Adjust To A Chair With Handle Support.



- L 180cm X W 60cm X H 50to80cm.
- Angle Of Front : 0° To 80°
- Front Sit: 60 X 70cm.
- Middle Sit: 60 X 45cm.
- Back Sit: 60 X 65cm.
- · Load Capasity: 225kg.
- Input Voltage: 230v Ac 50Hz.



- Time: 0 to 60 minutes Digital Timer with Audio Buzzer.
- Most Common and globally used modality designed to run constantly to complete the rush of patient.
- Variable power selection in 5 steps
- High speed cooling fan inside to cool valve tube.

TECHNICAL DETAIL:

• Input voltage: 230VAC, 50 Hz

Dimensions: (L20"x W12"xH30")

• Weight: 36 Kg. Approx

Output Power: 500 w of R.F.

Frequency: 27.12 MHz (Approx)

FREE ACCESSORIES:

One pair condenser pad & cable

OPTIONAL ACCESSORIES:

- Disc Electrodes
- · Optional card update to PEME systems

LC155 MOIST HEAT THERAPY



Also Available in 8 & 12 Pack Units

www.lifecarepmi.com



LC153 SHORT WAVE DIATHERMY 500 WATTS



FEATURES:

- Elegant Square Shaped Body.
- · Heavy Gauge Stainless Steel
- · Double Wall Body.
- MCB Swich for Mains Supply & Safety.
- · Heater Indicator for Heating Supply.
- · Caster Wheel for Easy Mobility.
- · Heavy Duty 2000W Heater.

TECHNICAL DETAIL:

· Input Voltage: 230VAC, 50Hz

Size: L 385 mm x W 340 mm x H 550 mm

· Weight: 15kg. Approx

FREE ACCESSORIES:

· Pack 4 No.



- · High Low Intensity Controller.
- · Height, Angle & Direction Adjustability.
- · Castor Wheeled Floor Model.

TECHNICAL DETAIL:

• Input voltage: 230VAC, 50 HZ

Weight: 9 Kg ApproxIR Lamp: 250 wattsTimer: 0 to 30 minutes

LC 011 UVR THERAPY



LC 261 INFRA RED LAMP



FEATURES:

- · Available with Mechanical Timer.
- · Height, Angle & Direction Adjustability.
- Castor wheeled floor model

TECHNICAL DETAIL:

• Input voltage: 230VAC, 50 Hz

Weight: 9.5 Kg Approx

IR and UVR

• Timer: 0 to 30 minutes



C. P. EQUIPMENT



CARE







GENERAL EQUIPMENTS



AN ISO 9001: 2015 AN ISO 13485: 2016 CERTIFIED COMPANY







Manufactured and Marketed by:

LIFE CARE PHYSIO MEDICAL INSTRUMENTS

Factory: C/4, Devashray Industrial Park, Nr. N. K. R. Engineering,

Opp. Srinand City, Phase IV, G.I.D.C., Vatva, Ahmedabad-382449.

Mob. : +91 9925165883, 9824445294

E-mail: lifecarepmi@yahoo.in, info@lifecarepmi.com

Visit us : www.lifecarepmi.com

Vadodara: F1/8, Zaver Society, Nr. Sangam Char Rasta,

Harni - Warasia Ring Road, Vadodara. M.: 99749 31532

Rajkot : H 7/10 HIG, Gujarat Housing, West Main Road, Nr. Astron Nala, B/h. Vikas Pharmacy,

Rajkot-360001. Email: lifecare.paresh21@gmail.com M.: 93270 36380

NOTE: As our products undergo continuous R & D for improvement, we reserve the right to change their specifications.